

**CONTRACT DOCUMENTS  
BOONE COUNTY, MISSOURI  
BID NO: 32-28APR05**

**ADDENDUM #1**  
**(Issued April 25, 2005)**

This addendum is issued in accordance with the Introduction and General Conditions of Bidding and is hereby incorporated into and made a part of the Contract Documents. Bidders are reminded that receipt of this addendum should be acknowledged and submitted with bidder's *Response Form*.

Specifications for the above noted Request for Bid and the work covered thereby are herein modified as follows, and except as set forth herein, otherwise remain unchanged and in full force and effect:

**BID DOCUMENTS:**

**Section 2.2.4. has been revised as follows:**

Cutting assembly shall have a hydraulic cylinder actuated retractable shield to shield cutting knives.

**Section 2.2.16. has been revised as follows:**

Cutting head shall have the capability of rotating 26 ° forward and 28 ° rearward with limited relief protection.

**Section 2.2.20. has been revised as follows:**


Lift control valve shall be a five (5) bank electro-hydraulic proportional, load sensing valve. This shall be included with the joystick option.

**Section 2.3.5. has been revised as follows:**

**Hydraulic System:** Pump shall be axial piston design mounted in line with crankshaft. Shall be 25 GPM minimum at 2,900 PSI at rated engine RPM. (Specifically excluding tandem driven hydraulic pumps.) Shall have 4-way, self-centering spools for 2, 3, or 4 hydraulic cylinders. Valve controls/circuits for mower to be mounted forward and to the right of operator's seat. Mower unit to be cable controlled, Vendor shall provide price for Joystick Control on response sheet. Joystick Control pricing shall include Lift control valve with a five (5) bank electro-hydraulic proportional, load sensing valve. Two (2) dual remote hydraulic circuits shall be mounted on rear of tractor.

**Section 2.3.19. has been revised as follows:**

**Operator's Station:** Cab shall be original equipment shock mounted to frame and unitized to power unit with full ROPS enclosed cab and limb risers for brush protection, heavy duty deluxe interior, **factory installed** am/fm stereo radio, front and rear windshield wipers/washers, sun visor, rubber floor mat, steps, handrails, tinted windows, dome light, fuel level gauge, engine coolant temperature gauge, engine oil pressure gauge, engine tachometer/ speedometer, hydraulic oil temperature gauge, and/or machine monitoring system with warning lights, horn, reverse warning alarm, inside rearview mirror(s), two (2) outside mirrors, contour full-suspension seat with arms, retractable seat belt, service hour meter, hand and foot throttle. Cab shall include a complete pressurized environmentally controlled system with heater, defroster, louvers, factory air conditioning, and air filtration/ventilation. A slow moving vehicle warning triangle shall be mounted on rear of tractor fender. Cab shall also have field office option.

By:   
Heather Turner, CPPB  
Buyer, Purchasing

BIDDER has examined copy of Addendum #1 to Bid Number 32-28APR05 Boom Mowers and Tractors, receipt of which is hereby acknowledged:

Company Name: \_\_\_\_\_

Address: \_\_\_\_\_  
\_\_\_\_\_

Phone Number: \_\_\_\_\_

Fax Number: \_\_\_\_\_

Authorized Representative Signature: \_\_\_\_\_

Date: \_\_\_\_\_

